

TSM-D

TUNNEL METAL DETECTOR FOR INDUSTRIAL USE

HIGH
IMMUNITY TO
ENVIRONMENTAL
INTERFERENCE



PROBE



ELECTRONIC
CONTROL UNIT

KEY FEATURES

- Detection of both magnetic and non-magnetic metals
- High immunity to environmental interference
- Installed without cutting conveyor belt
- Digital Programming
- Very high reliability
- IP65 main unit and probe



w w w . c e i a . n e t



Quality control at its finest

The **CEIA TSM-D digital Metal Detector** is suitable for intercepting magnetic and non-magnetic metal fragments of medium to large dimensions in industrial, textile, chemical, mining, foodstuffs and other products, both for quality control and machinery protection.


The product to be inspected is carried on a conveyor belt through the Detector Probe, which is connected to the Electronic Control Unit. The **TSM-D** Metal Detector probe unit can be opened up, thereby allowing installation on conveyor belts without cutting them. Detection sensitivity and other operational settings can be pre-selected digitally using function keys and alphanumeric display.

SPECIFICATIONS

DETECTION FUNCTIONS	Adjustable sensitivity
	Interception speed programmable according to applications (2 to 250 m/min)
	Digital programming with alphanumeric display
	Visual and acoustical indicator
	Built-in self-diagnosis system
	Built-in settings memory without backup battery
INPUTS / OUTPUTS	Programmable Alarm Relay: rating 30 Vac, 2.5A
	Encoder/Reset Input
	Standard bluetooth connectivity
POWER SUPPLY	100-240 Vac, 50/60 Hz, 1.5A max
ENVIRONMENTAL REQUIREMENTS	Operating temperature: -10 to +55 °C
	Relative humidity: 0 -95% (without condensation)
APPLICATIONS	Product Quality Control and protection of machinery in the following industries: <ul style="list-style-type: none"> • Textiles • Concrete • Timber • Chemicals • Mining • Paper • Foodstuffs • Clay
CERTIFICATION AND CONFORMITY	Conforms and is tested to European standards required for the CE mark
	Complies with EC regulations and international standards relating to electrical safety and electromagnetic compatibility
OTHER	Length of cable connecting main unit and probe: standard 3m, others on request. Conforms and is tested to European Standards required for the CE mark


DIMENSIONS (mm)

PROBE



W	500 ÷ 1500 in 100 mm increments	Dimensions of standard models (mm) Other sizes on request
H	200 ÷ 700 in 50 mm increments	

ELECTRONIC CONTROL UNIT



CEIA Costruzioni Elettroniche Automatismi Industriali
Zona Industriale 54, 52041 Vicinaggio - Arezzo (ITALY)
phone +39 0575 4181 • qa-detectors@ceia-spa.com



www.ceia.net

